COMFORT SENSORY FABRIC WALL PANELS

SPECIFICATION DATASHEET

APPLICABLE CLAUSES: UNICLASS - Ss 25 25 05 Acoustic Panel Systems

CWAS - K13 170 Acoustic Panel Lining

Description: Comfort Sensory Fabric Wrapped Wall Panels

System Performance: Class A – 80mm thick Direct Fix

System Supplier: London Wall Design Ltd

63 Barwell Business Park, Leatherhead Road


Chessington, KT9 2NY Tel: 0208 391 8750

Email: info@londonwall.co.uk

Web: Sound Absorption Products - London Wall

Battens: Non applicable, Direct Fix

Acoustic Performance:



Panelling: High Density Sound Absorbing Fibreboard Core finished in our standard range fabric, Camira Sonus, Lucia, Cara or Era (other finishes available on request).

Fire: Core Board EN13501-1:2018 A2-s1, d0 and Class O fire rating to BS476: Part 6

Sonus EN13501-1, Class B, s1, d0 Era EN13501-1, Class B, s1, d0

Lucia/Cara Class 1 to BS476: Part 7 and EN13501-1, Class B, s1, d0

Class O Fabrics can be supplied on request

Weight: 40mm thick = 10 kg/m2

Standard Panel Sizes: 1200mm (w) x 1200/2700mm (h)

Other sizes or site specific available on request

Dimension Tolerance of Panels: +/- 4mm

Installation: Concealed Fixing Plates and Adhesive