

CONCORD PERFORATED WALL PANELS

SPECIFICATION DATASHEET

APPLICABLE CLAUSES: UNICLASS - Ss 25 25 05 Acoustic Panel Systems
CWAS - K13 170 Acoustic Panel Lining

Description: Concord Perforated Wall Panels

System Performance: See Acousticians Report

System Supplier: London Wall Design Ltd
63 Barwell Business Park, Leatherhead Road
Chessington, KT9 2NY
Tel: 0208 391 8750
Email: info@londonwall.co.uk
Web: [Sound Absorption Products - London Wall](#)

Batten: Split batten concealed fixing system

Insulation: RWA45 Rockwool

Acoustic Performance: Upto Class C – 50mm Airgap

Perforations/Slots: 6mm, 8mm, 10mm & 12mm (Micro-Perforated available on request)

Hole/Slot Centres: 16mm / 32mm / 64mm (project specific size/patterns available)

Finishes: Birch Plywood, Veneers, LP/HP/CP Laminates, Painted to Colour Ref, Clear Lacquered

Core Material: Ply or MDF (Standard or FR)

Fire Resistance: Class1 or Class O (Euro Class B or C) Options Available

Backing Options: Black open weave/non-woven acoustically transparent

Weight: Design dependant

Max Panel Sizes: 1200mm (w) x 3000mm (h) Other site specific sizes available on request

Installation: Pinned & Glued or Split Batten