

HARMONY MODULAR SLATTED CEILING & WALL PANELS

SPECIFICATION DATASHEET

APPLICABLE CLAUSES: UNICLASS - Ss 25 25 05 Acoustic Panel Systems
CWAS - K13 170 Acoustic Panel Lining
UNICLASS - Ss 30 25 22 01 Acoustic Baffle Suspended Ceilings
CWAS – K40 Demountable Suspended Ceilings

Description: Harmony Modular Slatted Ceiling & Wall Panels

System Performance: See Acousticians Report

System Supplier: London Wall Design Ltd
63 Barwell Business Park, Leatherhead Road
Chessington, KT9 2NY
Tel: 0208 391 8750
Email: info@londonwall.co.uk
Web: [Sound Absorption Products - London Wall](#)

Batten: Split batten concealed fixing system

Hanging System: Kits includes Spiral hooks, wire, fixing anchor and easy adjust clamps

Insulation: RWA45 Rockwool

Acoustic Performance: Up to Class A – 50mm Airgap plus Minimum 40% Open Space

Timber Slat Options: 44mm (w) x 19mm (d), 44mm (w) x 44mm (d), 19mm (w) x 44mm (d),
Other sizes available on request

Timber Finishing: Clear Semi Matt Lacquer or Class O (Euro Class B) Lacquer

Backing Options: 12mm Black Compressed Eco Polyester EN13501-1:2007+A1:2009 Part 1:
Classification using data from reaction to fire tests, Class B or
MDF Perimeter Frame behind Macflex Black Fabric to BS5867 Part 2 Type B

Weight: Design dependant

Std Panel Sizes: 600mm (w) x 600mm (l), 600mm (w) x 1200mm (l), 600mm (w) x 1800mm (l),
600mm (w) x 2400mm (l),
Other site specific sizes available on request

Installation: Screw and Adhesive Direct fix – Split Batten hanging if airgap required. Or
fitted within a T24 Ceiling Grid Suspended from structure