

HARMONY SLATTED CEILING & WALL PANELS

SPECIFICATION DATASHEET

APPLICABLE CLAUSES: UNICLASS - Ss 25 25 05 Acoustic Panel Systems
CWAS - K13 170 Acoustic Panel Lining

Description: Harmony Slatted Ceiling & Wall Panels

System Performance: See Acousticians Report

System Supplier: London Wall Design Ltd
63 Barwell Business Park, Leatherhead Road
Chessington, KT9 2NY
Tel: 0208 391 8750
Email: info@londonwall.co.uk
Web: [Sound Absorption Products - London Wall](#)

Batten: Split batten concealed fixing system

Insulation: RWA45 Rockwool

Acoustic Performance: Up to Class A – 50mm Airgap plus Minimum 40% Open Space

Timber Slat Options: 44mm (w) x 19mm (d), 44mm (w) x 44mm (d), 19mm (w) x 44mm (d),
69mm (w) x 44mm (d) - Other sizes available on request

Timber Finishing: Clear Semi Matt Lacquer or Class O (Euro Class B) Lacquer

Backing Options: 12mm Black Compressed Eco Polyester EN13501-1:2007+A1:2009 Part 1:
Classification using data from reaction to fire tests, Class B or
MDF Perimeter Frame behind Macflex Black Fabric to BS5867 Part 2 Type B

Weight: Design dependant

Max Panel Sizes: 1200mm (w) x 2400mm (h) Other site specific sizes available on request

Installation: Screw and Adhesive Direct fix – Split Batten hanging if airgap required.