

SERENITY ACOUSTIC CEILING BAFFLE

SPECIFICATION DATASHEET

APPLICABLE CLAUSES: UNICLASS - Ss 30 25 22 01 Acoustic Baffle Suspended Ceilings
CWAS – K40 Demountable Suspended Ceilings

Description: Serenity Acoustic Ceiling Baffles

System Performance: NRC 1.0 – 24mm thick

System Supplier: London Wall Design Ltd
63 Barwell Business Park, Leatherhead Road
Chessington, KT9 2NY
Tel: 0208 391 8750
Email: info@londonwall.co.uk
Web: [Sound Absorption Products - London Wall](#)

Hanging System: Kits includes Spiral hooks, wire, fixing anchor and easy adjust clamps

Acoustic Performance:

Acoustic Absorber -		Baffles		Acoustic Baffle - 24mm			
Frequency (Hz)	125	250	500	1000	2000	4000	NRC
Baffles 24mm	0.45	0.60	1.00	1.00	1.00	1.00	1.00

Panelling: Eco-friendly Recycled Compressed Polyester from Plastic Bottles available in 23 different colours

Fire: EN13501-1:2007+A1:2009 Part 1: Classification using data from reaction to fire tests, Class B

Weight: 24mm thick = 4.5kg/m²

Standard Panel Sizes: Variety of shapes and sizes available, see brochure for details at...
[Serenity Acoustic Baffles - London Wall](#)

Installation: Standard method suspended via gripple wire method, grid framework optional.