

SERENITY ACOUSTIC CEILING BAFFLE

SPECIFICATION DATASHEET

APPLICABLE CLAUSES: UNICLASS - Ss 30 25 22 01 Acoustic Baffle Suspended Ceilings
CWAS – K40 Demountable Suspended Ceilings

Description: Serenity Acoustic Ceiling Grid

System Performance: NRC 0.95 – 12mm thick

System Supplier: London Wall Design Ltd
63 Barwell Business Park, Leatherhead Road
Chessington, KT9 2NY
Tel: 0208 391 8750
Email: info@londonwall.co.uk
Web: [Sound Absorption Products - London Wall](#)

Hanging System: Kits includes Spiral hooks, wire, fixing anchor and easy adjust clamps

Acoustic Performance:

Acoustic Absorber				Acoustic Grid - 12mm			
Frequency (Hz)	125	250	500	1000	2000	4000	NRC
Grid 12mm	0.40	0.85	1.00	0.96	1.00	1.00	0.95

Panelling: Eco-friendly Recycled Compressed Polyester from Plastic Bottles available in 23 different colours

Fire: EN13501-1:2007+A1:2009 Part 1: Classification using data from reaction to fire tests, Class B

Weight: 12mm thick = 4.5kg/m²

Design Options: Frost/Skyline/Spoon/Games/Bug/Track/Dusk/Chew/Slats

Standard Grid Sizes: 1200mm (w) x 1200mm (l), 1200mm x 2400mm, 2400mm x 2400mm

Installation: Standard method suspended via gripple wire method, grid framework optional.